



## Axial-Kugellagerring

■ axial

Art.-Nr.	für Ø-Stift	Ø	S	Tragzahl Stat. Kp	Material/ Oberfläche
04.520.0013.010	13 mm	22	8	260	St, gal verzinkt
04.520.1013.405	13 mm	22	8	195	Edelstahl V2A, blank
04.520.0014.010	14 mm	25	8,5	300	St, gal verzinkt
04.520.1014.405	14 mm	25	8,5	225	Edelstahl V2A, blank
04.520.0016.010	16 mm	27	9	350	St, gal verzinkt
04.520.1016.405	16 mm	27	9	260	Edelstahl V2A, blank
04.520.0020.010	20 mm	33	10	600	St, gal verzinkt
04.520.0022.010	22 mm	43	12	850	St, gal verzinkt
04.520.0026.010	26 mm	43	12	850	St, gal verzinkt

## Stahl- bzw. Messing-Zwischenring

■ gerundet

Art.-Nr.	für Ø-Stift	Ø	Material/ Oberfläche
04.521.0013.010	13 mm	21	St, gal verzinkt
04.521.0013.305	13 mm	21	Ms, blank
04.521.0014.010	14 mm	22	St, gal verzinkt
04.521.0014.305	14 mm	22	Ms, blank
04.521.0016.010	16 mm	29	St, gal verzinkt
04.521.0016.305	16 mm	29	Ms, blank
04.521.0020.010	20 mm	34	St, gal verzinkt
04.521.0020.305	20 mm	34	Ms, blank

## Messing-Zwischenring

■ gestanzt

Art.-Nr.	für Ø-Stift	Ø	S	Material/ Oberfläche
04.522.0005.305	5 mm	8	1,5	Ms, blank
04.522.0006.305	6 mm	10	1,7	Ms, blank
04.522.0007.305	7 mm	13	1,8	Ms, blank
04.522.0008.305	8 mm	13	1,8	Ms, blank
04.522.0009.305	9 mm	16	2,2	Ms, blank
04.522.0010.305	10 mm	16	2,2	Ms, blank
04.522.0011.305	11 mm	20	2,2	Ms, blank
04.522.0012.305	12 mm	20	2,7	Ms, blank

1

2

3

4

5

6

7

8

9

i