

Manufacturer's declaration on fire tests carried out with the
200 Series Product Family - Version 00

Issued by: Wilh. Schlechtendahl & Söhne GmbH & Co. KG
Hauptstraße 18 32
42579 Heiligenhaus

This manufacturer's declaration applies to the following lock and fitting designs in the tubular frame area:

- **Locks without panic function of series 100**
01.110/111..., 01.130/131...
- **Locks with panic function of series 100**
01.112/113..., 01.114/115..., 01.116/117..., 01.118/119..., 01.120/121..., 01.122/123...,
01.132/133..., 01.134/135..., 01.136/137..., 01.138/139...
- **Counter-Strike-Boxes of series 100**
01.144..., 01.146/147...
- **Panic fittings of series 100**
Panic bar handle 01.680/681/682/683/686/687/688/689...
Panic push bar 01.690/691/692/693...
- **Complementary accessories**
z.B. Latch 12mm, Top lock, Latch spring loaded, Connecting rods, Rod guides, Strike plates in different versions

List of fire tests

Item	1	
Profile system	Aluminum composite profile, thermally separated	
Door structure	2-leaf, glazed tubular frame swing door	
Which side was tested?	opposite hinge side	
Achieved classification	E30/ EI2 30/ EW 30	
Test report number	DMT-DO-50-079	

Basis of this manufacturer's declaration

Fire tests carried out in recognized test centers according to the previous listing.



Andreas Mielke, certified technician
CE-Commissioner

Heiligenhaus, 18.09.2024

(Place and date of issue)