

CONSTRUCTION PRODUCTS REGULATION (EU) 305/2011

DECLARATION OF PERFORMANCE DoP N° 009-01-EN

1. Unique identification code of the product type:

Emergency exit device for panic exit doors according to DIN EN 179:2008-04

0432-CPR-000037_01 – Version 01

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11 (4) of the CPR:

full frame doors – panic device

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

For doors on escape routes operated by a lever handle, type “A”

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11 (5):

**WSS - Wilh. Schlechtendahl & Söhne GmbH & Co. KG
Hauptstr. 18 - 32
42579 Heiligenhaus**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

N/A

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 1

7. MPA Dortmund, DAKKS no. 0432 (Germany's national accreditation body), has executed type testing in accordance with the provisions of DIN EN 179:2008-04, has carried out assessment and verification of constancy of performance and has issued the test report.

8. European Technical Assessment:

N/A

9. Declared performance

Harmonised technical specification: DIN EN 179:2008-04

| Essential characteristics | Performance |
|---|--|
| Ability to release (for doors on escape routes) | |
| 4.1.2 Release function | < 1 sec |
| 4.1.3 Release operation | The release direction of the device is in the direction of the door opening |
| 4.1.4 Lever handle design | The device releases the door following a movement of the lever handle in a downward rotational direction |
| 4.1.5 Push pad design | It does not apply to this device |
| 4.1.6 Double doorset | It does not apply to this device |
| 4.1.8 Exposed edges and corners | > 0,5 mm |
| 4.1.11 Push pad installation | It does not apply to this device |
| 4.1.12 Lever handle installation | X > 120 mm; Z < 150 mm |
| 4.1.13 Operating element projection | Category 2: projection up to 100 mm |
| 4.1.14 Operating element face | V > 18 mm; operating face of the lever handle: thickness > 5 mm and rounded surface radius > 5 mm |
| 4.1.15 Lever handle free end | U > 40 mm; W < 100 mm; $\alpha < 30^\circ$ |
| 4.1.16 Lever handle operating gap | The test block passes freely between the lever handle and the surface of the door |
| 4.1.17 Push pad operating gap | It does not apply to this device |
| 4.1.18 Test rod | The device does not trap the test rod in any position of the lever handle |
| 4.1.19 Push pad release operation | It does not apply to this device |
| 4.1.20 Accessible gap | The test piece placed in any accessible gap cannot prevent the correct operation of the device |
| 4.1.21 Door free movement | The device does not include any element impeding the free movement of the door once it is released |
| 4.1.22 Top vertical bolt | It does not apply to this device |
| 4.1.24 Keepers | The keeper protects the door frame from the damage which may be caused by the door closing and opening. |
| 4.1.25 Keepers dimensions | It does not apply to this device |
| 4.1.27 Door mass and dimensions | Mass \leq 200 Kg, height \leq 2520 mm, width \leq 1320 mm |
| 4.1.28 Outside access device (OAD) | The OAD does not render the panic device inoperable from the inside |
| 4.2.2 Release forces | < 70 N |
| 4.2.7 Security requirements | Grade 2: the device remains in the locked position when a force of 1 000 N is applied to the door |
| Durability of ability to release against aging and degradation (for doors on escape routes) | |
| 4.1.7; 4.2.9 Corrosion resistance | Grade 3: high resistance (96 hours) |
| 4.1.23; 4.2.6 Covers for vertical rods | It does not apply to this device |
| 4.1.26 Lubrication | Every 20 000 test cycles without dismantling the device |
| 4.2.3 Re-engagement force | < 50 N |
| 4.2.4; 4.1.21 4.2.2; 4.2.3 Durability | Grade 7: 200 000 test cycles |
| 4.2.5 Abuse resistance-Operating element | Perpendicular pull force <1 000 N, parallel force <500 N |
| 4.2.6 Abuse resistance-Vertical rod | It does not apply to this device |
| 4.2.8; 4.2.2; 4.1.21 Final examination | The device is released with a force of < 70 N and the door moves freely once the device is released |
| Self closing ability C (for fire/smoke doors on escape routes) | |
| 4.2.3 Re-engagement force | < 50 N |
| Durability of Self closing ability C against aging and degradation (for fire/smoke doors on escape routes) | |
| 4.2.4 Durability | Grade 7: 200 000 test cycles |
| 4.2.3 Re-engagement force | < 50 N |
| Resistance to fire E (Integrity) and I (Insulation) (for fire doors on escape routes) | |
| 4.1.10; Suitability of emergency exit devices for smoke/fire resisting doorsets– Annex B: Additional requirements | yes |
| Control of Dangerous substances | |

| | |
|-----------------------------|--|
| 4.1.29 Dangerous substances | The materials in this product do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations |
|-----------------------------|--|

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.
Signed for and on behalf of the manufacturer by:



Andreas Mielke, certified technician
CE-Commissioner

Heiligenhaus, 27. April 2020

(Place and date of issue)

CE-MARKING

relating to the Declaration of Performance no. 009-01-EN BauPVo (EU Nr. 305/2011)
for panic devices according to DIN EN 179:2008-04

| | | | | | | | | | | |
|--|---|---|---|---|---|---|---|---|---------|--|
| CE | | | | | | | | | | |
| Wilh. Schlechtendahl & Söhne GmbH & Co. KG Hauptstraße 18 – 32 42579 Heiligenhaus | | | | | | | | | | |
| 2015 | | | | | | | | | | |
| Germany | | | | | | | | | | |
| DoP-No. 009-01-EN BauPVO (EU Nr. 305/2011) | | | | | | | | | | |
| 0432-CPR-000037-01 Version 01 | | | | | | | | | | |
| full frame- panic device | | | | | | | | | | |
| EN 179:2008-04 | | | | | | | | | | |
| 3 | 7 | 6 | B | 1 | 3 | 2 | 2 | A | A/B/C/D | |



Andreas Mielke, certified technician
CE-Commissioner

Heiligenhaus, 27. April 2020

(Place and date of issue)

22.01.2021

REACH – Verordnung / RoHS

As a company based in the European Union which deeply cares about health and environmental protection, we respect the EU decree 1907/2006/EG, dedicated to the registration, evaluation and authorization of chemicals (REACH) as well as the guideline RoHS 2011/65/EU.

Wilh. Schlechtendahl & Söhne GmbH & Co.KG (WSS) has analyzed the legal provisions comprehensively with regard to its own activities and comes to the following conclusion:

WSS is not a manufacturer of chemicals or preparations and does not place such products on the market. In accordance with the regulation, we are therefore to be classified as a downstream user and here in particular as an industrial user and product manufacturer. Therefore, a registration of substances is not required for our products.

We have advised our suppliers of the obligation to provide information in accordance with Article 33 of the REACH Regulation and would like to pass on the information we have received as follows.

According to the current status, lead (Pb) Cas-No. 7439-92-1 may be present in our products at a concentration of more than 0.1% by mass in steel, aluminum and brass alloys. However, the lead is bound in the corresponding alloys and is not released when the products are used as intended.

In addition, we continue to identify our process auxiliaries as well as the substances used in the products and analyze the areas of application in order to be able to derive potentially necessary measures.

Mit freundlichen Grüßen / With kind regards

i.A. Andreas Wolter
Wilh. Schlechtendahl & Söhne GmbH & Co. KG
Hauptstrasse 18-32
42579 Heiligenhaus
Germany

Manufacturer's Declaration of Factory Production Control

The system of factory production control of Wilh. Schlechtendahl & Söhne GmbH & Co. KG meets the requirements of product standard DIN EN 179:2008-04 and DIN EN 1125:2008-04.

Heiligenhaus, May 2013