

CONSTRUCTION PRODUCTS REGULATION (EU) 305/2011

DECLARATION OF PERFORMANCE DoP N°010-01-EN

1. Unique identification code of the product type:

**panic device according to DIN EN 1125:2008-04
0432-CPR-000037-02 Version 01**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

Full frame - panic device

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

For doors on escape routes

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11 (5):

**WSS - Wilh. Schlechtendahl & Söhne GmbH & Co. KG
Hauptstr. 18 - 32
42579 Heiligenhaus**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

N/A

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 1

7. The MPA NRW, DAKKS no. 0432 (Germany's national accreditation body), has executed type testing in accordance with the provisions of DIN EN 1125:2008-04, has carried out assessment and verification of constancy of performance and has issued the test report.

8. European Technical Assessment:

N/A

9. Declared performance

Harmonised technical specification EN 1125:2008-04

Essential characteristics	Performance
Ability to release (for doors on escape routes)	
4.1.2 Release function	< 1 sec
4.1.3 Panic exit device mounting	Mounted on the inside face of the door
4.1.5 Exposed edges and corners	> 0,5
4.1.7 Double doorset	applicable
4.1.9 Bar installation	Z < 150 mm
4.1.10 Bar length	X > 60% X
4.1.11 Bar projection	Category 2: W < 100 mm
4.1.12 Bar end	The operating bar does not protrude beyond either of the end support brackets
4.1.13 Operating bar face	V > 18 mm
4.1.14 Test rod	passed
4.1.15 Door face gap	R > 25 mm
4.1.16 Accessible gap	passed
4.1.17 Door free movement	passed
4.1.18 Top vertical bolt	applicable
4.1.20 Keepers	passed
4.1.21 Keepers dimensions	does not apply to this device
4.1.23 Door mass and dimensions	Mass ≤ 200 Kg, height ≤ 2520 mm, width ≤ 1320 mm
4.1.24 Outside access device	passed
4.2.2 Release forces	< 80 N with the door unloaded, and < 220 N with the door loaded with 1000 N
4.2.7 Security requirement	Grade 2: the device remains locked when a force of 1000 N is applied to the door
Durability of ability to release against aging and degradation (for doors on escape routes)	
4.1.4; 4.2.9 Corrosion resistance	Grade 3: high resistance (96 hours)
4.1.6 Temperature range	-10°C; +60°C not more than 50% as they are at 20°C
4.1.19 4.2.6 Covers for vertical rods	It does not apply to this device
4.1.22 Lubrication	Every 20 000 test cycles without dismantling the device
4.2.3 Re-engagement force	< 50 N
4.2.4 Durability	Grade 7: 200 000 test cycles
4.2.5 Abuse resistance –Horizontal bar	1 000 N
4.2.6 Abuse resistance –Vertical rod	does not apply to this device
4.2.8; 4.2.2; 4.1.17 Final examination	The device is released with a force of 80 N, with the door unloaded, and of 220 N, with the door loaded with 1 000 N, and the door moves freely
Self closing ability C (for fire/smoke doors on escape routes)	
4.2.3 Re-engagement force	< 50 N
Durability of self closing ability C (against aging and degradation) (for fire/smoke doors on escape routes)	
4.2.4 Durability	Grade 7: 200 000 test cycles
4.2.3 Re-engagement force	< 50 N
Resistance to fire E (integrity) and I (insulation) (for fire doors on escape routes)	
4.1.8; Annex B Suitability of panic exit devices for use on fire/smoke resisting door assemblies –	Grade B: suitable for use on fire/smoke resisting door assemblies
Control of Dangerous substances	
4.1.25 dangerous substances	The materials in this product do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.
Signed for and on behalf of the manufacturer by:



Andreas Mielke, certified technician
CE-Commissioner

Heiligenhaus, 27. April 2020

(Place and date of issue)

CE-MARKING

relating to the Declaration of Performance no. 010-01-EN BauPVo (EU Nr. 305/2011)
for single-axis door h according to DIN EN 1125:2008-04

CE										
Wilh. Schlechtendahl & Söhne GmbH & Co. KG Hauptstraße 18 – 32 42579 Heiligenhaus										
2015										
Germany										
DoP-Nr. 010-01-EN BauPVO (EU Nr. 305/2011)										
0432-CPR_000037-02 Version 01										
Full frame - panic device										
EN 1125:2008-04										
3	7	6	B	1	3	2	2	A/B	A/B/C	



Andreas Mielke, certified technician
CE-Commissioner

Heiligenhaus, 27.04.20

(Place and date of issue)

22.01.2021

REACH – Verordnung / RoHS

As a company based in the European Union which deeply cares about health and environmental protection, we respect the EU decree 1907/2006/EG, dedicated to the registration, evaluation and authorization of chemicals (REACH) as well as the guideline RoHS 2011/65/EU.

Wilh. Schlechtendahl & Söhne GmbH & Co.KG (WSS) has analyzed the legal provisions comprehensively with regard to its own activities and comes to the following conclusion:

WSS is not a manufacturer of chemicals or preparations and does not place such products on the market. In accordance with the regulation, we are therefore to be classified as a downstream user and here in particular as an industrial user and product manufacturer. Therefore, a registration of substances is not required for our products.

We have advised our suppliers of the obligation to provide information in accordance with Article 33 of the REACH Regulation and would like to pass on the information we have received as follows.

According to the current status, lead (Pb) Cas-No. 7439-92-1 may be present in our products at a concentration of more than 0.1% by mass in steel, aluminum and brass alloys. However, the lead is bound in the corresponding alloys and is not released when the products are used as intended.

In addition, we continue to identify our process auxiliaries as well as the substances used in the products and analyze the areas of application in order to be able to derive potentially necessary measures.

Mit freundlichen Grüßen / With kind regards

i.A. Andreas Wolter
Wilh. Schlechtendahl & Söhne GmbH & Co. KG
Hauptstrasse 18-32
42579 Heiligenhaus
Germany

Manufacturer's Declaration of Factory Production Control

The system of factory production control of Wilh. Schlechtendahl & Söhne GmbH & Co. KG meets the requirements of product standard DIN EN 179:2008-04 and DIN EN 1125:2008-04.

Heiligenhaus, May 2013