



PIV Prüfinstitut Schlösser und Beschläge Velbert  
Wallstraße 41 – D 42551 Velbert  
Director of Institute: Andrea Horsthemke (B.Eng.)  
Tel 0049-(0)2051-9506 5  
Fax 0049-(0)2051-9506 69  
eMail: [info@piv-velbert.de](mailto:info@piv-velbert.de)



1309

## Certificate of Constancy of Performance

**1309 - CPR - 0304**

(Version: 06)

In accordance with the EU Regulation No 305/2011 of the European Parliament and of the Council from 09. March 2011 (Construction Products Regulation or CPR) this certificate shall apply to the construction product

**Mortise lock Series 200**  
Item number: see Annex to the Certificate

placed on the market under the name or the trade name of

**Wilh. Schlechtendahl & Söhne GmbH & Co. KG**  
Hauptstr. 18-32  
D-42579 Heiligenhaus

and produced in the manufacturing facility

**D-42579 Heiligenhaus**  
Hauptstr. 18-32

This certificate attests that all provisions of the assessment and verification of constancy of the performance according to the description in annex ZA of the standard

**EN 1125:2008**

within the scope of the system 1 for the performance according to the information given in this certificate, and that

**the performance of the construction product is consistently rated as resistant.**

**Product classification key see Annex to the Certificate**

This certificate was initially created on the **17. December 2015** and shall remain valid until either the harmonized standard of the construction product, the system of assessment and verification of constancy of performance or the production conditions at the plant are changed, or suspended until the certificate of the notified certification body is suspended or revoked.

D-Velbert, 22. December 2020

This certificate has a total of 11 pages  
and replaces the certificate no. 1309-CPR-0304,  
version 05 from 21.02.2019.



  
Andrea Horsthemke (B.Eng.)  
Head of Certification Body



PIV Prüfinstitut Schlösser und Beschläge Velbert  
 Wallstraße 41 – D 42551 Velbert  
 Director of Institute: Andrea Horsthemke (B.Eng.)  
 Tel 0049-(0)2051-9506 5  
 Fax 0049-(0)2051-9506 69  
 eMail: [info@piv-velbert.de](mailto:info@piv-velbert.de)



1309

## Annex for the Certificate of Constancy of Performance

### 1309 - CPR – 0304

(Version: 06)

Essential features	Sections of this European standard	Mandated levels and/or classes	Notes
<b>Ability for release</b> (of doors in escape routes) Release function Attachment of the panic door lock Protruding edges and corners Double-leaf door Installation of the control rod Length of the control rod Protrusion of the control panel End of the control rod Actuating surface of the rod Test rod Free space of the door leaf surface Accessible free space Free movement of the door Upward running driving bolt rods Locking counterparts Dimensions of the locking counterparts Dimensions and mass of the door External access device Release forces Requirements towards security (burglary protection)	4.2.1	none	$\leq 1$ s passed $\geq 0.5$ mm passed $Z \leq 150$ mm $\geq 60\%$ Class 1 ( $W \leq 150$ mm) Class 2 ( $W \leq 100$ mm) passed $V \geq 18$ mm passed $R \geq 25$ mm 20 mm passed passed passed $H \leq 15$ mm; $M \leq 45^\circ$ ; $P \leq 3$ mm $\leq 1600$ mm width, $\leq 3500$ mm height, door mass class 7 (400 kg) passed $\leq 80$ N and $\leq 220$ N under 1000 N pressure Class 2



PIV Prüfinstitut Schlösser und Beschläge Velbert  
 Wallstraße 41 – D 42551 Velbert  
 Director of Institute: Andrea Horsthemke (B.Eng.)  
 Tel 0049-(0)2051-9506 5  
 Fax 0049-(0)2051-9506 69  
 eMail: [info@piv-velbert.de](mailto:info@piv-velbert.de)



1309

## Annex for the Certificate of Constancy of Performance

### 1309 - CPR – 0304

(Version: 06)

Essential features	Sections of this European standard	Mandated levels and/or classes	Notes
<p><b>Lasting functionality in terms of the ability for release compared with aging and loss of quality</b>            (for doors in escape routes)</p> <p>Corrosion resistance</p> <p>Temperature range</p> <p>Covers for driving bolt rods</p> <p>Lubrication</p> <p>Closing force</p> <p>Lasting functionality</p> <p>Resistance of the control element against misuse</p> <p>Resistance of the driving bolt rod against abuse</p> <p>Final examination</p>	4.2.1	none	<p style="text-align: center;">Class 3: 96 h</p> <p style="text-align: center;">Actuating force at -10°C and +60°C            &lt; 50% of the measured actuating force at +20°C</p> <p style="text-align: center;">NPD</p> <p style="text-align: center;">20,000 cycles</p> <p style="text-align: center;">≤ 50 N</p> <p style="text-align: center;">Application area of the door of class A and B: 200,000 cycles, class 7</p> <p style="text-align: center;">Application area of the door of class C: 20,000 cycles, class 7</p> <p style="text-align: center;">1000 N</p> <p style="text-align: center;">NPD</p> <p style="text-align: center;">≤ 80 N and            ≤ 220 N under 1000 N pressure</p>
<p><b>Ability to close automatically</b>  <b>Close C</b>            (of fire protection doors/smoke protection doors in escape routes)</p> <p>Closing force</p>	4.2.1	none	≤ 50N



PIV Prüfinstitut Schlösser und Beschläge Velbert  
Wallstraße 41 – D 42551 Velbert  
Director of Institute: Andrea Horsthemke (B.Eng.)  
Tel 0049-(0)2051-9506 5  
Fax 0049-(0)2051-9506 69  
eMail: [info@piv-velbert.de](mailto:info@piv-velbert.de)



1309

## Annex for the Certificate of Constancy of Performance

1309 - CPR – 0304

(Version: 06)

Essential features	Sections of this European standard	Mandated levels and/or classes	Notes
<b>Lasting functionality in terms of the ability for the ability to close automatically compared with aging and loss of quality</b> (of fire protection doors/smoke protection doors in escape routes) Lasting functionality  Closing force	4.2.1	none	Application area of the door of class A and B: 200,000 cycles, class 7 Application area of the door of class C: 20,000 cycles, class 7 ≤ 50N
<b>Fire resistance capabilities E (room closure) and I (thermal insulation)</b> (of fire protection doors in escape routes)	4.2.1	none	Class 0 Class B: Fire assessment no. DMT-DO-50-423, D-Lathen from 27.07.2017
<b>Control of hazardous substances</b>	4.1.25 ZA.1	none	passed: The manufacturer declares that the product contains no hazardous substances or release them beyond the maximum levels specified in European standards and national regulations.





PIV Prüfinstitut Schlösser und Beschläge Velbert  
 Wallstraße 41 – D 42551 Velbert  
 Director of Institute: Andrea Horsthemke (B.Eng.)  
 Tel 0049-(0)2051-9506 5  
 Fax 0049-(0)2051-9506 69  
 eMail: [info@piv-velbert.de](mailto:info@piv-velbert.de)



1309

## Annex for the Certificate of Constancy of Performance

### 1309 - CPR – 0304

(Version: 06)

No	Item-No.	Description	Function	Vs-Type	Back-set	Distance	Forend in mm	Accessories/ Note	Classification												Cmb	Bar
									1	2	3	4	5	6	7	8	9	10	11	12		
13	14.280.xxxx.426	Panic keep (Sv+ 200)	la	C	30-80		≥22	Switch lock 14.288.xxxx.426	3	7	7	B	1	3	2	1/2**	A/B	C	3/4/7/8/11/12/17/18/21/22/25/26	102/ 112/ 122/132/ 142/152		
14	14.280.xx136.426	Panic keep with rod barrier (Sv+200)	la	C	30-80		≥22	Switch lock 14.288.xxxx.426	3	7	7	0	1	3	2	1/2**	A/B	C	3/4/7/8/11/12/17/18/21/22/25/26	102/ 112/ 122/132/ 142/152		
15	14.160.xxxx.426	Panic lock	Function "E", 1-leaf, rs/lS	I	B	29-45	92 mm PZ/ 94 mm RZ	≥22		3	7	7	B*	1	3	2	1/2**	A/B	B	-	101/ 111/ 121/131/ 141/151	
16	14.172.xxxx.426	Panic lock with additional locking		I	B	29-45	92 mm PZ/ 94 mm RZ	≥22	Catch bolt lock 14.290.xxxx.426 - 12mm stroke and 16mm protrude/ latch 14.320.0000.010 - 12mm stroke	3	7	7	B*	1	3	2	1/2**	A/B	B	-	101/ 111/ 121/131/ 141/151	
17	14.166.xxxx.426	Panic lock	Function "E", 2-leaf, rs/lS	I	A	29-45	92 mm PZ/ 94 mm RZ	≥22		3	7	7	B*	1	3	2	1/2**	A/B	A	13/ 14 29/ 30	101/ 111/ 121/131/ 141/151	
18	14.178.xxxx.426	Panic lock with additional locking		I	A	29-45	92 mm PZ/ 94 mm RZ	≥22	Catch bolt lock 14.290.xxxx.426 - 12mm stroke and 16mm protrude/ latch 14.320.0000.010 - 12mm stroke	3	7	7	B*	1	3	2	1/2**	A/B	A	13/ 14 29/ 30	101/ 111/ 121/131/ 141/151	
19	14.164.xxxx.426	Panic lock	Function "B", 1-leaf, rs/lS	IV	B	29-45	92 mm PZ/ 94 mm RZ	≥22		3	7	7	B	1	3	2	1/2**	A/B	B	-	101/ 111/ 121/131/ 141/151	
20	14.176.xxxx.426	Panic lock with additional locking		IV	B	29-45	92 mm PZ/ 94 mm RZ	≥22	Catch bolt lock 14.290.xxxx.426 - 12mm stroke and 16mm protrude/ latch 14.320.0000.010 - 12mm stroke	3	7	7	B	1	3	2	1/2**	A/B	B	-	101/ 111/ 121/131/ 141/151	
21	14.170.xxxx.426	Panic lock	Function "B", 2-leaf, rs/lS	IV	A	29-45	92 mm PZ/ 94 mm RZ	≥22		3	7	7	B	1	3	2	1/2**	A/B	A	13/ 14 29/ 30	101/ 111/ 121/131/ 141/151	
22	14.182.xxxx.426	Panic lock with additional locking		IV	A	29-45	92 mm PZ/ 94 mm RZ	≥22	Catch bolt lock 14.290.xxxx.426 - 12mm stroke and 16mm protrude/ latch 14.320.0000.010 - 12mm stroke	3	7	7	B	1	3	2	1/2**	A/B	A	13/ 14 29/ 30	101/ 111/ 121/131/ 141/151	
23	14.162.xxxx.426	Panic lock	Function "D", 1-leaf, rs/lS	IIIb	B	29-45	92 mm PZ/ 94 mm RZ	≥22		3	7	7	B	1	3	2	1/2**	A/B	B	-	101/ 111/ 121/131/ 141/151	
24	14.174.xxxx.426	Panic lock with additional locking		IIIb	B	29-45	92 mm PZ/ 94 mm RZ	≥22	Catch bolt lock 14.290.xxxx.426 - 12mm stroke and 16mm protrude/ latch 14.320.0000.010 - 12mm stroke	3	7	7	B	1	3	2	1/2**	A/B	B	-	101/ 111/ 121/131/ 141/151	



PIV Prüfinstitut Schlösser und Beschläge Velbert  
 Wallstraße 41 – D 42551 Velbert  
 Director of Institute: Andrea Horsthemke (B.Eng.)  
 Tel 0049-(0)2051-9506 5  
 Fax 0049-(0)2051-9506 69  
 eMail: [info@piv-velbert.de](mailto:info@piv-velbert.de)



1309

## Annex for the Certificate of Constancy of Performance

### 1309 - CPR – 0304

(Version: 06)

No.	Item-No.	Description		Function	Vs-Type	Backset	Distance	Forend in mm	Accessories/ Note	Classification										Cmb	Bar
										3	7	7	B	1	3	2	1/2**	A/B	A		
25	14.168.xxxx.426	Panic lock		IIIb	A	29-45	92mm PZ/ 94mm RZ	≥22mm		3	7	7	B	1	3	2	1/2**	A/B	A	13/ 14 29/ 30	101/ 111/ 121/131/ 141/151
26	14.180.xxxx.426	Panic lock with additional locking	Function "D", 2-leaf, rs/rs	IIIb	A	29-45	92mm PZ/ 94mm RZ	≥22mm	Catch bolt lock 14.290.xxxx.426 - 12mm stroke and 16mm protrude/latch 14.320.0000.010 - 12mm stroke	3	7	7	B	1	3	2	1/2**	A/B	A	13/ 14 29/ 30	101/ 111/ 121/131/ 141/151
27	14.145.xxxx.426	Latch lock		-	B	29-45	92mm PZ/ 94mm RZ	≥22mm		3	7	7	B	1	3	2	1/2**	A/B	B	-	101/ 111/ 121/131/ 141/151
28	14.159.xxxx.426	Latch lock with additional locking	with transmission function, without latch, rs/rs	-	B	29-45	92mm PZ/ 94mm RZ	≥22mm	Catch bolt lock 14.290.xxxx.426 - 12mm stroke and 16mm protrude/latch 14.320.0000.010 - 12mm stroke	3	7	7	B	1	3	2	1/2**	A/B	B	-	101/ 111/ 121/131/ 141/151
29	14.284/285.xxxx.426	Panic keep with E-opener	14.284.xxxx.426 DIN right/ 14.285.xxxx.426 DIN left	Ia	C	34-80		≥22mm	Switch lock 14.288.xxxx.426/catch 14.294.xxxx.405	3	7	7	B	1	3	2	1/2**	A	C	3/4/ 7/8/ 11/ 12/ 17/ 18/ 21/ 22/ 25/ 26	102/ 112/ 122/132/ 142/152
30	14.284/285.xx136.426	Panic keep with E-opener and rod barrier	14.284.xx136.426 DIN right/ 14.285.xx136.426 DIN left	Ia	C	34-80		≥22mm	Switch lock 14.288.xxxx.426/catch 14.294.xxxx.405	3	7	7	0	1	3	2	1/2**	A	C	3/4/ 7/8/ 11/ 12/ 17/ 18/ 21/ 22/ 25/ 26	102/ 112/ 122/132/ 142/152

\* - optional equipping with a secured latch locking device – necessary modification of classification:

x	x	x	0	x	x	x	x	x	x	x
---	---	---	---	---	---	---	---	---	---	---

\*\* When using panic bars no. 121-142, the 8th digit in the classification key applies:

x	x	x	x	x	x	x	x	1	x	x
---	---	---	---	---	---	---	---	---	---	---

Applies for all lock varieties: Distance 92 mm for profile cylinder  
 Distance 94 mm for round cylinder  
 Forend ≥ 22 mm

Max. weight door leaf 400 kg  
 Max. height 3.500 mm  
 Max. width 1.600 mm

Vs-Type (Device-Types)	
Vs-Type A	Device for the active leaf 2-leaf doors & for 1-leaf doors
Vs-Type B	Device for 1-leaf doors outward opening
Vs-Type C	Device for the inactive leaf 2-leaf doors



PIV Prüfinstitut Schlösser und Beschläge Velbert  
Wallstraße 41 – D 42551 Velbert  
Director of Institute: Andrea Horsthemke (B.Eng.)  
Tel 0049-(0)2051-9506 5  
Fax 0049-(0)2051-9506 69  
eMail: [info@piv-velbert.de](mailto:info@piv-velbert.de)



1309

## Annex for the Certificate of Constancy of Performance

### 1309 - CPR – 0304

(Version: 06)

Function descriptions	
Function "I"	One-piece lock follower, permanent escape door function. It is always possible to open from the inside via the fitting. From the outside, the latch and the bolt can be retracted using the key. (Switching function E)
Function "Ia"	One-piece lock follower, permanent escape door function. It is always possible to open both leaves using the inactive leaf from the inside via the fitting. (Keep)
Function "IIIb"	Split lock follower, permanent escape door function from the inside. It is always possible to open from the inside via the fitting. The external fitting constantly has an effect on the lock latch. The bolt is only activated from the outside using the key. After an actuation from the inside, the door cannot even be opened from the outside until it is manually locked again. (Transit function D)
Function "IV"	Split lock follower, permanent escape door function from the inside. It is always possible to open from the inside via the fitting. The external fitting is constantly engaged or released using the key. The bolt is only activated from the outside using the key. After an actuation from the inside, the door cannot even be opened from the outside by means of the fitting. (Toggle function B)
Function "IVa"	Split lock follower, permanent escape door function from the inside. It is always possible to open from the inside via the fitting. In the basic position, the door locks automatically and the external fitting is released. The external fitting can be permanently engaged or released (basic position) using the key. After an actuation from the inside, the door cannot be opened from the outside by means of the fitting, when it's in the basic position. (Toggle function B)
Function "VIa"	Split lock follower, permanent escape door function from the inside. It is always possible to open from the inside via the fitting. In the basic position, the door locks automatically and the external fitting is released. The external fitting can be engaged using the key or electrically. After an actuation from the inside, the door cannot be opened from the outside by means of the fitting, when it's in the basic position. (Electric handle control EDS)





PIV Prüfinstitut Schlösser und Beschläge Velbert  
 Wallstraße 41 – D 42551 Velbert  
 Director of Institute: Andrea Horsthemke (B.Eng.)  
 Tel 0049-(0)2051-9506 5  
 Fax 0049-(0)2051-9506 69  
 eMail: [info@piv-velbert.de](mailto:info@piv-velbert.de)



1309

## Annex for the Certificate of Constancy of Performance

### 1309 - CPR – 0304

(Version: 06)

Approved panic bars

No.	Designation	Type	Length of rod	Rod profile	Protection caps
101	14.484.0000.xxx	Pushbar active leaf	500-650 mm length of rod	Al E4/C-0 silver coloured or stainless steel look	
	14.484.1000.xxx		651-800 mm length of rod		
	14.484.2000.xxx		801-950 mm length of rod		
	14.484.3000.xxx		951-1100 mm length of rod		
	14.484.4000.xxx		1101-1250 mm length of rod		
	14.484.5000.xxx		Special length		
102	14.492.0000.xxx	Pushbar inactive leaf	500-650 mm length of rod		
	14.492.1000.xxx		651-800 mm length of rod		
	14.492.2000.xxx		801-950 mm length of rod		
	14.492.3000.xxx		951-1100 mm length of rod		
	14.492.4000.xxx		1101-1250 mm length of rod		
	14.492.5000.xxx		Special length		
111	14.400.0000.xxx	Pushbar PS 99 Design-Line active leaf	with KS-Distance piece, 1.200 mm length of rod	Al E4/C-0 silver coloured or stainless steel look	
	14.404.0000.xxx		with LM- Distance piece, 1.200 mm length of rod		
	14.410.0000.xxx		with LED-Distance piece, 1.200 mm length of rod		
112	14.440.0000.xxx	Pushbar Design-Line inactive leaf	with KS-Distance piece, 1.200 mm length of rod	Al E4/C-0 silver coloured or stainless steel look	
	14.444.0000.xxx		with LM-Distance piece, 1.200 mm length of rod		
	14.450.0000.xxx		with LED-Distance piece, 1.200 mm length of rod		
121	14.400.1000.xxx	Pushbar PS 128 Design-Line active leaf	with KS- Distance piece, 1.200 mm length of rod	Stainless steel	
	14.420.1000.xxx		with KS- Distance piece, 1.500 mm length of rod		
122	14.440.1000.xxx	Pushbar PS 128 Design-Line inactive leaf	with KS- Distance piece, 1.200 mm length of rod	Stainless steel	
	14.460.1000.xxx		with KS- Distance piece, 1.500 mm length of rod		
131	14.400.2000.xxx	Pushbar PS 128 Alu round active leaf	with KS- Distance piece, 1.200 mm length of rod	Al E4/C-0 silver coloured or stainless steel look	
	14.420.2000.xxx		with KS- Distance piece, 1.500 mm length of rod		
132	14.440.2000.xxx	Pushbar PS 128 Alu round inactive leaf	with KS- Distance piece, 1.200 mm length of rod	Al E4/C-0 silberfarbig oder Edeldstahloptik	
	14.460.2000.xxx		with KS- Distance piece, 1.500 mm length of rod		



PIV Prüfinstitut Schlösser und Beschläge Velbert  
 Wallstraße 41 – D 42551 Velbert  
 Director of Institute: Andrea Horsthemke (B.Eng.)  
 Tel 0049-(0)2051-9506 5  
 Fax 0049-(0)2051-9506 69  
 eMail: [info@piv-velbert.de](mailto:info@piv-velbert.de)



1309

## Annex for the Certificate of Constancy of Performance

### 1309 - CPR – 0304

(Version: 06)

No.	Designation	Type	Length of rod	Rod profile	Protection caps
141	ECO EPN IV 27°	Eco Pushbar active leaf for PZ 92 and RZ 94 DO 20.1	up to 1.500 mm length of rod	Aluminum coated or stainless steel	
142	ECO EPN IV 45°	Eco Pushbar inactive leaf for PZ 92 and RZ 94 DO 20.1	up to 1.500 mm length of rod	Aluminum coated or stainless steel	
151	14.40x.300x.xxx	Pushbar PS 99 Series 200	1.200 mm length of rod	Al E4/C-0 silver coloured or stainless steel look	
	14.42x.300x.xxx	DIN R/ DIN L active leaf	1.500 mm length of rod		
152	14.44x.300x.xxx	Pushbar PS 99 Series 200	1.200 mm length of rod	Al E4/C-0 silberfarbig oder Edelstahl	
	14.46x.300x.xxx	DIN R/ DIN L inactive leaf	1.500 mm length of rod		

#### Approved accessories

Item-No.	Description	
01.824.xxxx.010/426	Rod guides	with flat- or U-Forend
14.292.xxxx.426	Rod guides spring supported	for door heights above 2,50 m up to max. 3,50 m
14.370.xxxx.426	Rod guides with hopper	with flat- or U-Forend
14.300.xxxx.426	Striking plate, bottom	adjustable
14.302.xxxx.426	Striking plate, top	for catch bolt lock and switch lock
14.306/307.xxxx.426	Striking plate, top for E-opener	14.306... DIN right/ 14.307... DIN left
14.321.xxxx.405	Latch guide/keeper as of 35 mandrel	for catch bolt lock and switch lock
14.322.xxxx.405	Latch guide/keeper for 30/34 mandrel	for catch bolt lock and switch lock
14.320.0000.010	Locking unit, top	to hammering
14.324.0000.010	Locking unit, bottom	to hammering
14.340.xxxx.426	Flat 270/320 x (≥22) x 3 mm	Flat 270/320 x (≥22) x 3 mm
14.342.xxxx.426	U-Form 268/318 x (≥24) x (≥6) mm	U-Form 268/318 x (≥24) x (≥6) mm
01.711.xxxx.426	Flat 270/320 x (≥24) x 3 mm	Flat 270/320 x (≥24) x 3 mm
01.825.1500.010	Connecting rod M5 x 1.550 mm	Ø6 mm
14.323.2000.010	Connecting rod M5 x 2.000 mm	Ø6 mm
14.323.2500.010	Connecting rod M5 x 2.500 mm	Ø6 mm
14.323.xxxx.010	Connecting rod M5 x xxxx mm	Ø10 mm - for locking nach unten downward only
957063/ 957073	Striking plate set, top, adjustable	for locking to the top and switch lock



PIV Prüfinstitut Schlösser und Beschläge Velbert  
 Wallstraße 41 – D 42551 Velbert  
 Director of Institute: Andrea Horsthemke (B.Eng.)  
 Tel 0049-(0)2051-9506 5  
 Fax 0049-(0)2051-9506 69  
 eMail: [info@piv-velbert.de](mailto:info@piv-velbert.de)



1309

## Annex for the Certificate of Constancy of Performance

### 1309 - CPR – 0304

(Version: 06)

Special striking plates/ Door opener / Special hardware for the external side

Alternatively to the standard strike plates, the locks can be fitted with special strike plates and electric operating-circuit door openers from the series	
<b>effeff Model series:</b>	142, 143, 131, 111, 19, 116, 118 und 119
<b>WSS-Model series:</b>	50032728, 50032729, 50032730, 50032731, 50032732, 50032733, 50032735, 50032736, 50032737, 50032738, 50032739, 50032926
<b>DORMA Model series:</b>	Fire 447, Smoke 117
<b>IST Systems Model series:</b>	FT 200, FT 201, FT 500, FT 501, R 7000, R 7001, A 7000
or optionally, with dummy strikes that are adapted to the respective door opener. When using the aforementioned door opener, it may possibly be necessary to adapt the fire protection classification (4th position of the classification key) of the locks.	
For the fittings 101 / 102/ 111/ 112, special fittings from the SALTO XS4 model series according to P-120003012 by SALTO Systems S.L. can also be used as outer fittings. The fitting must be labelled with the code DO 20.52.	

If an external access device is envisaged for use with a knob cylinder, neither the size nor the position of the knob (turning handle) can impede the actuation of the emergency exit lock.