



PIV Prüfinstitut Schlösser und Beschläge Velbert  
Wallstraße 41 – D 42551 Velbert  
Director of Institute: Andrea Horsthemke (B.Eng.)  
Tel 0049-(0)2051-9506 5  
Fax 0049-(0)2051-9506 69  
eMail: [info@piv-velbert.de](mailto:info@piv-velbert.de)



1309

## Certificate of Constancy of Performance

1309 - CPR - 0371

(Version: 03)

In accordance with the EU Regulation No 305/2011 of the European Parliament and of the Council from 09. March 2011 (Construction Products Regulation or CPR) this certificate shall apply to the construction product

### Mortise lock Series 200

Item numbers: 14.140..., 14.144..., 14.146..., 14.156 and 14.158...  
with the striker plates 14.340..., 14.341..., 14.342... and 01.711...

placed on the market under the name or the trade name of

**Wilh. Schlechtendahl & Söhne GmbH & Co. KG**  
Hauptstraße 18 – 32  
D-42579 Heiligenhaus

and produced in the manufacturing facility

**D-42579 Heiligenhaus**  
Hauptstraße 18 – 32

This certificate attests that all provisions of the assessment and verification of constancy of the performance according to the description in annex ZA of the standard

**EN 12209:2003 / AC:2005**

within the scope of the system 1 for the performance according to the information given in this certificate, and that

**the performance of the construction product is consistently rated as resistant.**

**Product classification key see Annex to the Certificate.**

This certificate was initially created on the **18. July 2017** and shall remain valid until either the harmonized standard of the construction product, the system of assessment and verification of constancy of performance or the production conditions at the plant are changed, or suspended until the certificate of the notified certification body is suspended or revoked.

Stamp certification body

D-Velbert, 21. February 2019

This certificate has a total of 6 pages  
and replaces the certificate no. 1309-CPR-0371,  
version 02 from 13. February 2018.



Andrea Horsthemke (B.Eng.)  
Manager of the Notified body



PIV Prüfinstitut Schlösser und Beschläge Velbert  
 Wallstraße 41 – D 42551 Velbert  
 Director of Institute: Andrea Horsthemke (B.Eng.)  
 Tel 0049-(0)2051-9506 5  
 Fax 0049-(0)2051-9506 69  
 eMail: [info@piv-velbert.de](mailto:info@piv-velbert.de)



1309

## Annex for the Certificate of Constancy of Performance

1309 - CPR - 0371

(Version: 03)

| Essential features   | Sections of this European standard | Mandated levels and/or classes | Notes   |
|--|------------------------------------|--------------------------------|---|
| Ability to close automatically   | 5.4.2<br>5.1.2                     |                                | Grade 9 (max. 400 kg door mass, max. 15 N closing force): Passed<br><br>≥ 2,5N: Passed  |
| Lasting functionality in terms of automatic closing  | 5.3.1                              |                                | Grade S (200 000 cycles, 50 N load on latch bolt): Passed   |
| Ability to keep the door in the closed position, and do not contribute to the spread of fire | 5.5                                |                                | Grade 1<br>Test report-No. DMT-DO-50-397,<br>DMT GmbH & Co. KG / Germany<br>from 29.06.2017   |
| Control of hazardous substances  | 5.1.1                              |                                | The manufacturer declares that the product contains no hazardous substances or release them beyond the maximum levels specified in European standards and national regulations. |



*Horsthemke*  
 Andrea Horsthemke (B.Eng.)  
 Manager of the Notified body



PIV Prüfinstitut Schlösser und Beschläge Velbert  
 Wallstraße 41 – D 42551 Velbert  
 Director of Institute: Andrea Horsthemke (B.Eng.)  
 Tel 0049-(0)2051-9506 5  
 Fax 0049-(0)2051-9506 69  
 eMail: [info@piv-velbert.de](mailto:info@piv-velbert.de)



1309

## Annex for the Certificate of Constancy of Performance

1309 - CPR - 0371

(Version: 03)

### Product matrix

| Classification key<br>Drop-latch lock with transmission (14.140...) |                                  |                             |   |        |                                      |                               |                           |                                   |                            |                    |
|---|----------------------------------|-----------------------------|---|--------|--------------------------------------|-------------------------------|---------------------------|-----------------------------------|----------------------------|--------------------|
| 1   | 2                                | 3                           | 4                                       | 5      | 6                                    | 7                             | 8                         | 9                                 | 10                         | 11                 |
| Category of use   | Durability and load on latchbolt | Door mass and closing force | Suitability for use on fire/smoke doors | Safety | Corrosion resistance and temperature | Security and drill resistance | Field of door application | Type of key operation and locking | Type of spindle operations | Key identification |
| 3   | S                                | 9                           | 1                                       | 0      | F                                    | 4                             | B                         | A                                 | 2                          | 0                  |

Forend version: Width: 22, 24, 28, 29,5 mm

Forend material: Stainless steel

Backset: 24, 30, 35, 40 and 45 mm

Distance: 92 mm PZ / 94 mm RZ

Follower version: Steel follower

Follower square: 9 mm

| Classification key<br>Latch lock with transmission (14.144...) |                                  |                             |   |        |                                      |                               |                           |                                   |                            |                    |
|--|----------------------------------|-----------------------------|---|--------|--------------------------------------|-------------------------------|---------------------------|-----------------------------------|----------------------------|--------------------|
| 1  | 2                                | 3                           | 4                                       | 5      | 6                                    | 7                             | 8                         | 9                                 | 10                         | 11                 |
| Category of use  | Durability and load on latchbolt | Door mass and closing force | Suitability for use on fire/smoke doors | Safety | Corrosion resistance and temperature | Security and drill resistance | Field of door application | Type of key operation and locking | Type of spindle operations | Key identification |
| 3  | S                                | 9                           | 1                                       | 0      | F                                    | --                            | B                         | A                                 | 2                          | 0                  |

Forend version: Width: 22, 24, 28, 29,5 mm

Forend material: Stainless steel

Backset: 24, 30, 35, 40 and 45 mm

Distance: 92 mm PZ / 94 mm RZ

Follower version: Steel follower

Follower square: 9 mm



*Horsthemke*  
 Andrea Horsthemke (B.Eng.)  
 Manager of the Notified body



PIV Prüfinstitut Schlösser und Beschläge Velbert  
 Wallstraße 41 – D 42551 Velbert  
 Director of Institute: Andrea Horsthemke (B.Eng.)  
 Tel 0049-(0)2051-9506 5  
 Fax 0049-(0)2051-9506 69  
 eMail: [info@piv-velbert.de](mailto:info@piv-velbert.de)



1309

## Annex for the Certificate of Constancy of Performance

1309 - CPR - 0371

(Version: 03)

### Product matrix

| Classification key<br>Drop-latch lock with transmission and additional locking (14.146...) |                                  |                             |   |        |                                      |                               |                           |                                   |                            |                    |
|--|----------------------------------|-----------------------------|---|--------|--------------------------------------|-------------------------------|---------------------------|-----------------------------------|----------------------------|--------------------|
| 1  | 2                                | 3                           | 4                                       | 5      | 6                                    | 7                             | 8                         | 9                                 | 10                         | 11                 |
| Category of use  | Durability and load on latchbolt | Door mass and closing force | Suitability for use on fire/smoke doors | Safety | Corrosion resistance and temperature | Security and drill resistance | Field of door application | Type of key operation and locking | Type of spindle operations | Key identification |
| 3  | S                                | 9                           | 1                                       | 0      | F                                    | 4                             | B                         | A                                 | 2                          | 0                  |

Forend version: Width: 22, 24, 28, 29,5 mm

Forend material: Stainless steel

Backset: 24, 30, 35, 40 and 45 mm

Distance: 92 mm PZ / 94 mm RZ

Follower version: Steel follower

Follower square: 9 mm

| Classification key<br>Drop-latch lock Function L+W with transmission and additional locking (14.156...) |                                  |                             |   |        |                                      |                               |                           |                                   |                            |                    |
|---|----------------------------------|-----------------------------|---|--------|--------------------------------------|-------------------------------|---------------------------|-----------------------------------|----------------------------|--------------------|
| 1   | 2                                | 3                           | 4                                       | 5      | 6                                    | 7                             | 8                         | 9                                 | 10                         | 11                 |
| Category of use   | Durability and load on latchbolt | Door mass and closing force | Suitability for use on fire/smoke doors | Safety | Corrosion resistance and temperature | Security and drill resistance | Field of door application | Type of key operation and locking | Type of spindle operations | Key identification |
| 3   | S                                | 9                           | 1                                       | 0      | F                                    | 3                             | B                         | A                                 | 2                          | 0                  |

Forend version: Width: 22, 24, 28, 29,5 mm

Forend material: Stainless steel

Backset: 30, 35, 40 and 45 mm

Distance: 92 mm PZ / 94 mm RZ

Follower version: Steel follower

Follower square: 9 mm



*Horsthemke*  
 Andrea Horsthemke (B.Eng.)  
 Manager of the Notified body



PIV Prüfinstitut Schlösser und Beschläge Velbert  
 Wallstraße 41 – D 42551 Velbert  
 Director of Institute: Andrea Horsthemke (B.Eng.)  
 Tel 0049-(0)2051-9506 5  
 Fax 0049-(0)2051-9506 69  
 eMail: [info@piv-velbert.de](mailto:info@piv-velbert.de)



1309

## Annex for the Certificate of Constancy of Performance

1309 - CPR - 0371

(Version: 03)

### Product matrix

| Classification key  |                                  |                             |  |        |                                      |                               |                           |                                   |                            |                    |
|---|----------------------------------|-----------------------------|--|--------|--------------------------------------|-------------------------------|---------------------------|-----------------------------------|----------------------------|--------------------|
| Latch lock with transmission and additional locking (14.158...) |                                  |                             |  |        |                                      |                               |                           |                                   |                            |                    |
| 1   | 2                                | 3                           | 4  | 5      | 6                                    | 7                             | 8                         | 9                                 | 10                         | 11                 |
| Category of use   | Durability and load on latchbolt | Door mass and closing force | Suitability for use on fire/ smoke doors | Safety | Corrosion resistance and temperature | Security and drill resistance | Field of door application | Type of key operation and locking | Type of spindle operations | Key identification |
| 3   | S                                | 9                           | 1  | 0      | F                                    | --                            | B                         | A                                 | 2                          | 0                  |

Forend version: Width: 22, 24, 28, 29,5 mm

Forend material: Stainless steel

Backset: 24, 30, 35, 40 and 45 mm

Distance: 92 mm PZ / 94 mm RZ

Follower version: Steel follower

Follower square: 9 mm



*Horsthemke*  
 Andrea Horsthemke (B.Eng.)  
 Manager of the Notified body



PIV Prüfinstitut Schlösser und Beschläge Velbert  
 Wallstraße 41 – D 42551 Velbert  
 Director of Institute: Andrea Horsthemke (B.Eng.)  
 Tel 0049-(0)2051-9506 5  
 Fax 0049-(0)2051-9506 69  
 eMail: [info@piv-velbert.de](mailto:info@piv-velbert.de)



1309

## Annex for the Certificate of Constancy of Performance

1309 - CPR - 0371

(Version: 03)

### Product matrix

| Classification key<br>Stainless steel-Striker plate Series 200: flat, 270x24x3 mm, 3-part screwed (14.341...) |                                  |                             |  |        |                                      |                               |                           |                                   |                            |                    |
|---|----------------------------------|-----------------------------|--|--------|--------------------------------------|-------------------------------|---------------------------|-----------------------------------|----------------------------|--------------------|
| 1   | 2                                | 3                           | 4  | 5      | 6                                    | 7                             | 8                         | 9                                 | 10                         | 11                 |
| Category of use   | Durability and load on latchbolt | Door mass and closing force | Suitability for use on fire/ smoke doors | Safety | Corrosion resistance and temperature | Security and drill resistance | Field of door application | Type of key operation and locking | Type of spindle operations | Key identification |
| 3   | S                                | 9                           | 1  | 0      | F                                    | 4                             | B                         | A                                 | 2                          | 0                  |

| Classification key<br>Stainless steel-Striker plate Series 200: flat, 270x24x3 mm, 2-part screwed (14.340...) |                                  |                             |  |        |                                      |                               |                           |                                   |                            |                    |
|---|----------------------------------|-----------------------------|--|--------|--------------------------------------|-------------------------------|---------------------------|-----------------------------------|----------------------------|--------------------|
| 1   | 2                                | 3                           | 4  | 5      | 6                                    | 7                             | 8                         | 9                                 | 10                         | 11                 |
| Category of use   | Durability and load on latchbolt | Door mass and closing force | Suitability for use on fire/ smoke doors | Safety | Corrosion resistance and temperature | Security and drill resistance | Field of door application | Type of key operation and locking | Type of spindle operations | Key identification |
| 3   | S                                | 9                           | 1  | 0      | F                                    | 3                             | B                         | A                                 | 2                          | 0                  |

| Classification key<br>Stainless steel-Striker plate Series 200: U-Form, 268x24x3 mm, 2-part screwed (14.342...) |                                  |                             |  |        |                                      |                               |                           |                                   |                            |                    |
|---|----------------------------------|-----------------------------|--|--------|--------------------------------------|-------------------------------|---------------------------|-----------------------------------|----------------------------|--------------------|
| 1   | 2                                | 3                           | 4  | 5      | 6                                    | 7                             | 8                         | 9                                 | 10                         | 11                 |
| Category of use   | Durability and load on latchbolt | Door mass and closing force | Suitability for use on fire/ smoke doors | Safety | Corrosion resistance and temperature | Security and drill resistance | Field of door application | Type of key operation and locking | Type of spindle operations | Key identification |
| 3   | S                                | 9                           | 1  | 0      | F                                    | 3                             | B                         | A                                 | 2                          | 0                  |

| Classification key<br>Stainless steel-Striker plate Series 200: flat, 270x24x3 mm, 2-part screwed, for E-Opener/Insert piece (01.711...) |                                  |                             |  |        |                                      |                               |                           |                                   |                            |                    |
|--|----------------------------------|-----------------------------|--|--------|--------------------------------------|-------------------------------|---------------------------|-----------------------------------|----------------------------|--------------------|
| 1  | 2                                | 3                           | 4  | 5      | 6                                    | 7                             | 8                         | 9                                 | 10                         | 11                 |
| Category of use  | Durability and load on latchbolt | Door mass and closing force | Suitability for use on fire/ smoke doors | Safety | Corrosion resistance and temperature | Security and drill resistance | Field of door application | Type of key operation and locking | Type of spindle operations | Key identification |
| 3  | S                                | 9                           | 1  | 0      | F                                    | 3                             | B                         | A                                 | 2                          | 0                  |



*Horsthemke*

Andrea Horsthemke (B.Eng.)  
 Manager of the Notified body